



# Bellwether Coffee

Electric. Ventless. Automatic.

## Bellwether Shop Roaster.

An integrated, cloud-connected system for sourcing and roasting sustainable, high quality coffee in any location. No installation or experience required.

The Bellwether Shop Roaster is a small format, high-throughput roaster with a 1.5 kilo capacity with optional continuous roasting up to 20 kilos in a single operation.



626 mm (25 in)

1.7 M  
(67 in)

925 mm  
(36.5 in)



626 mm (25 in)

### Countertop Roaster

- ☒ 1.5 kg (3.3 lb) Capacity
- 🕒 3-4 Roasts an Hour
- 👤 2 mins of Labor per roast

### Continuous Roasting Upgrade

- ☒ 20 kg Autoloader and Base
- ☒ Up to 13 Continuous Roasts
- 👤 5 mins of Labor per 20 kg

## All-Electric

- No installation required
- Plug in and roast from day one
- No gas lines, venting or construction

## Ventless

- Roast in any location
- First and only commercial coffee roaster designed for ventless use
- Eliminates harmful VOCs

## Automatic

- Fully automated roasting - no experience required

## Integrated

- Internal afterburner eliminates smoke
- Integrated web app to order coffee and manage your account from any device
- Click-and-ship green coffee marketplace features a global library of fresh, seasonal, sustainable coffees with custom roast profiles

## Sustainable

- The world's lowest carbon coffee
- Industry-leading farmer equity standards
- Reduces CO2 from roast cycle by 87%

## Dimensions (W x H x D)

- Roaster - 626 mm (25 in) x 925 mm (36.5 in) x 711 mm (27 in)
- Autoloader - 626 mm (25 in) x 390 mm (15.4 in) x 608 mm (24 in)
- Base Cabinet - 626 mm (25 in) x 460 mm (18 in) x 640 mm (25.2 in)
- Total Configuration - 626 mm (25 in) x 1.7 M (67 in) x 711 mm (27 in)

## Weight

- Roaster - 123.57 kg (272 lb)
- Autoloader - 21.4 kg (47 lb)
- Base Cabinet - 34 kg (75 lb)
- Total Configuration - 178.97 kg (395 lb)

## Electrical Specs

- 200-240 VAC, 1-phase
- 30amp circuit (5kw machine)
- 50-60 Hz
- NEMA L6-30P plug, standard locking plug for 240v service, the standard cord is 2 M (6 FT)

## Clearance

- Clearance requirements for both the delivery path and installation area - minimum 2" clearance on both sides (50mm each side)

## Cleaning and Maintenance

- Customers will need to empty the chaff can, water reservoir, and clean the prefilter. (when prompted)

## Certifications

- UL 197
- UL 710
- NSF4 Food Safety



**Bellwether  
Coffee**