ICB TF 1.0 Gal PE, 120/240V SST

Height: 25.2" Width: 12.1" Depth: 24.3" (64.0cm) (30.7cm) (61.7cm)



- Intuitive 4.3" touchscreen with user interface provides an enhanced experience when operating and programming the brewers
- SmartWAVE sprayhead technology creates an industry best uniformity of extraction for exceptionally smooth tasting coffee
- Platinum Edition SmartWave technology delivers a timed air purge at the end of the brew cycle, removing residual water from the sprayhead, reducing lime build up and ultimately extending the life of the equipment
- USB port for easy programming
- Digital readout displays in English, Spanish, or French ---for easier programming and control
- Energy-saver mode reduces tank temperature during idle periods
- Electronic funnel lock prevents removal of each brew funnel until drip-through is complete
- ICB TF 54300.0100 is compatible with new TF 1.0-gallon Baseless ThermoFresh® Servers, all previous generations of TF 1.0-gallon Baseless TF Servers, and Airpots
- PROP 65 Warning Decal included in packaging with equipment
- · Servers not included unless otherwise noted

Server(s) sold separately

Agency:





Specifications

Product #: 54300.0100 Funnel: Smart Funnel

Water Access: Plumbed Faucet: Side

Interface: Wireless Legs: 4" Satin Nickel Legs

Finish: Stainless

Additional Features

BrewWISE

Electrical & Capacity

Volts*	Amps		Attached Plug Typ	Plug Type	236ml cups/hr Temp. 163 60°F (15.5°C)	Phase	plus Ground	Hertz 60	
) / I/ #		201	Cord	D. T	8oz cups/hr	Input H ² O		# Wires	

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

Plumbing Requirements

	1 lambing requirements								
PSI		kPa Fitting Supplied		Water Flow Required (GPM)					
	20-90 138-621		3/8" Male Flare Fitting	1.00					


CAD Drawings


2D	Revit	KLC
•	•	•


MARNING: This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



BUNN® reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. For most current specifications and other info visit bunn.com.







Unit				Shipping				
	Height	Width	Depth	Height	Width	Depth	Weight	Volume
English	25.2 in.	12.1 in.	24.3 in.	30.8 in.	17.5 in.	26.7 in.	63.000 lbs	8.311 ft ³
Metric	64.0 cm	30.7 cm	61.7 cm	78.1 cm	44.5 cm	67.8 cm	28.577 kgs	0.235 m³



Related Products & Accessories: ICB TF 1.0 Gal PE, 120/240V SST(54300.0100)



FILTERS, GOURMET 500 500/1 50/CL

Product #: 20138.1000



STAND ASSY, TF SERVER GEN3

Product #: 39795.0200



STAND ASSY KIT, TF SERVER

Product #: 54473.1000

FUNNEL ASSY, SST INFUSION COFFEE

Product #: 54675.0001



Serving & Holding Options: ICB TF 1.0 Gal PE, 120/240V SST(54300.0100)



TF SERVER, 1G DSG GEN3

Product #:42700.0200



TF SERVER, 1G DSG GEN3 NOBASE

Product #:42700.0250



TF SERVER, 1.5G DSG GEN3

Product #:42750.0200



TF SERVER, 1.5G DSG GEN3 NOBASE

Product #:42750.0250



TF SERVER, 1G MECH GEN3

Product #:44000.0200



TF SERVER, 1G MECH GEN3 NOBASE

Product #:44000.0250



TF SERVER, 1.5G MECH GEN3

Product #:44050.0200



TF SERVER, 1.5G MECH NOBASE GEN3

Product #:44050.0250

