



7 ANOMALIES - CAUSES - REMEDIES

The table shows the possible anomalies that can cause a failure and/or irregular operation of the A||Ground^{sense} coffee grinder. For each anomaly, the possible cause that generated it and the actions to be taken to restore correct functioning of the appliance are indicated.

Anomaly	Cause	Solution
The grinder does not turn on.	No electric power.	<p>Make sure that the switch is in the "ON" position;</p> <p>Make sure that the circuit breaker upstream of the socket (if present) is in the ON position.</p> <p>Make sure that the power cord is intact and that the plug is properly connected to the socket.</p>
Coffee beans do not descend from the supply hopper.	Shutter closed too much.	Open the shutter.
<p>The display shows the "Warning" screen:</p> 	The adjustment ring nut has been released from its rotation lane and the safety microswitch (see Fig. 6 Part 1) does not detect the removable chamber in its correct working position.	Correctly secure the adjustment ring nut in its rotation lane following the instructions given under "Reassembling the grinder" in section 6.1.1.
<p>When the grinding cycle starts, the display shows one of the following screens:</p> 	The instant weighing system is active but does not detect the presence in the fork of the "filter holder cup" (espresso), of the moka "filter", or the collection "container" of the filter dose.	<p>Place the "filter holder cup" or the moka "filter" or the collection "container" of the filter dose on the fork, then press the start grinding button again corresponding to the desired dose.</p> <p>Note: for the instant weighing system to work properly, it must detect the presence on the fork of the corresponding filter or collection container, depending on the set grind.</p>

Anomaly	Cause	Solution
The motor stops during grinding.	Motor protection thermal cut-out intervention due to blocking of the grinding system in the presence of objects or foreign bodies between the grinders.	<p>Turn off the appliance and wait for it to cool completely.</p> <p>Disconnect the appliance from the power supply.</p> <p>Close the shutter and remove the supply hopper.</p> <p>Open the removable chamber and clean the grinders and remove any foreign bodies.</p> <p>Reassemble the appliance and start a grinding cycle.</p>



ATTENTION! If the anomaly persists even after carrying out the suggested corrective actions, or if functional anomalies not listed in the table occur, contact a specialist technician and have the appliance checked.

8 REQUESTING SPARE PARTS

If the parts of your grinder need to be replaced, original spare parts can be ordered either from the **Fiorenzato M.C. S.r.l.** spare parts service, or from an Authorised Service Centre or Dealer.



ATTENTION! Remember that the interventions to replace the grinders and in general all the internal parts of the grinder must be carried out by specialist technical personnel.



ATTENTION! Fiorenzato M.C. S.r.l. is not responsible for any injury to persons and/or damage to the appliance caused by the replacement of components with non-original spare parts and performed by unqualified personnel.