



MVP Specifications



MVP2



MVP3

Electrical

Steam

Brew

	Voltage, Single Phase	Amps, Max Draw	Cord Plug Rating, Amps (UL)	Watts per Element	Total Wattage	Tank Capacity, Liters	Watts per Element	Total Wattage	Tank Capacity, Liters
2-Group	220	28	30	2000 x 2	4000	7.7	700 x 2	1400	1.9 x 2
3-Group	220	36	50	2500 x 2	5000	12.3	700 x 3	2100	1.9 x 3

Machine Dimensions

Plumbing

	Height	Width (Inch / mm)	Depth	Machine Weight (Lbs / Kgs)	Shipping Weight (Lbs / Kgs)	Shipping Dimensions L x W x H (Inch / mm)	Direct Connection (Compression)
2-Group	21 / 534	30 / 762	24 / 610	154 / 70	267 / 121	33 x 36 x 30 / 838 x 914 x 762	3/8" OD
3-Group	21 / 534	41 / 1042	24 / 610	190 / 86	343 / 156	33 x 46 x 30 / 838 x 1168 x 762	3/8" OD

- Certified by Intertek (ETL) for Sanitation to NSF / ANSI 4
- Certified by Intertek (ETL) for Electrical Safety to ANSI / UL 197
- Certified by Intertek (ETL) for Electrical Safety to CSA C22.2 No. 109
- Certified by KTR for Korean KC Mark
- Certified to IECEE CB Scheme
- CE Compliant (By request)
- C-Tick Compliant (By request)
- Sabre Compliant (By request)

